

DC Voltage/Current Generators/Calibrators

For Evaluating and Calibrating Precision Instruments and Circuits

R6144/6142

Specifications

Voltage/Current Generation

Voltage generation range:

Range	Voltage generating/range (R6144/6142)	Setting resolution
10 mV	0 to ± 16.000 mV/ ± 11.999 mV	1 μ V
100 mV	0 to ± 160.00 mV/ ± 119.99 mV	10 μ V
1 V	0 to ± 1.6000 mV/ ± 1.1999 mV	100 μ V
10 V	0 to ± 16.000 mV/ ± 11.999 mV	1 mV
30 V (R6144 only)	0 to ± 32.000 V	2 mV

Current generation range:

Range	Voltage generating/range (R6144/6142)	Setting resolution
10 mA	0 to ± 1.6000 mA/ ± 1.1999 mA	100 nA
100 mA	0 to ± 16.000 mA/ ± 11.999 mA	1 μ A
100 mA	0 to ± 160.00 mA/ ± 119.99 mA	10 μ A

Overall accuracy: Guaranteed for 6 months (including linearity) at 23°C $\pm 5^\circ\text{C}$, RH 70% max., with constant power and load conditions.

Range	Generating accuracy $\pm$ (% of setting + range error)
10 mV	0.03 + 5 μ V
100 mV	0.03 + 25 μ V
1 V	0.03 + 200 μ V
10 V	0.03 + 2 mV
30 V (R6144 only)	0.03 + 4 mV
1 mA	0.035 + 300 nA
10 mA	0.035 + 3 μ A
100 mA	0.04 + 30 μ A

One-day stability: Under temperatures of 23°C $\pm 5^\circ\text{C}$ and relative humidity of 70% or less with constant power supply and load.

Range	Generating stability $\pm$ (% of setting + range error)
10 mV	0.01 + 5 μ V
100 mV	0.01 + 10 μ V
1 V	0.01 + 50 μ V
10 V	0.01 + 200 μ V
30 V (R6144 only)	0.01 + 300 μ V
1 mA	0.01 + 20 nA
10 mA	0.01 + 200 nA
100 mA	0.01 + 2 μ A

Temperature coefficient: From 0°C to +50°C, per 1°C

Range	Generating temperature coefficient $\pm$ (ppm/°C of set. ++ range error/°C)
10 mV	20 + 200 nV
100 mV	20 + 2 μ V
1 V	20 + 10 μ V
10 V	20 + 40 μ V
30 V (R6144 only)	60 + 4 μ V
1 mA	20 + 4 nA
10 mA	20 + 40 nA
100 mA	20 + 400 nA

Maximum load and output resistance: 4-wire resistance for 1 V, 10 V and 30 V ranges and 2-wire resistance for the other ranges

Range	Maximum load current/voltage	Output resistance
10 mV	0.8 μ A (R6144), 0.6 μ A (R6142)*	Approx. 2 Ω
100 mV	8 μ A (R6144), 6 μ A (R6142)*	
1 V	Source: 160 mA (R6144)	0.4 m Ω max.
10 V	120 mA (R6142)	4 m Ω max.
30 V (R6144 only)	Sink: 100 mA	8 m Ω max.
1 mA	28 V output follow-up voltage (R6144) 10 V output follow-up voltage (R6142)	100 M Ω min.
10 mA		10 M Ω min.
100 mA		1 M Ω min.

* 20 k Ω load equivalent to 0.01% error

Output noise: At 1 k Ω load resistance for 1 mA, 10 mA and 100 mA ranges

Range	Frequency	100 Hz	10 kHz	20 Hz to 20 MHz
10 mA		5 μ Vp-p	10 μ Vp-p	3 mVp-p
100 mA		15 μ Vp-p	30 μ Vp-p	
1 V		80 μ Vp-p	150 μ Vp-p	
10 V		200 μ Vp-p	500 μ Vp-p	
30 V (R6144 only)		400 μ Vp-p	1 mVp-p	
1 mA		30 nAp-p	150 nAp-p	6 μ Ap-p
10 mA		300 nAp-p	400 nAp-p	
100 mA		3 μ Ap-p	4 μ Ap-p	

Line regulation: $\pm 0.005\%$ of range or less (R6144), $\pm 0.007\%$ of range or less (R6142) at rated voltage - 15% to + 10%.

Load regulation: ± 0.005 of range or less at maximum load when 4-wire connected (except for 10 mV and 100 mV ranges)

Maximum load capacity and inductance:

Range	Maximum load capacity	Maximum load inductance
1, 10, 30 V	1000 μ F	500 μ F
1, 10, 100 mV	100 μ F	1 mH

* The maximum load capacity for 1, 10, 100 mA and inductance for 1 V, 10 V and 30 V are measured when the limiter is activated at the maximum setting.

Settling time: Time for output to reach an expected value $\pm 0.1\%$ when the limiter is activated at maximum setting from zero to full scale.

Range	Load requirement	Over/under shoot	Settling time
All ranges	Maximum load resistance	Expected value $\pm 0.1\%$	50 ms max.
1/10/30 V ranges	Load at 30 μ F capacity		50 ms max.
	Load at 100 μ F capacity		60 ms max.

* Maximum load resistance in current ranges: Maximum load voltage/resistance value by full scale

Operating conditions: Ambient temperature 0°C to +50°C

Relative humidity 85% max. (no condensation)

Storage conditions: Ambient temperature -25°C to +70°C

Power supply: 90 VAC to 110 VAC, 48 to 66 Hz

Options

Option No.	Standard	32	42	44
Supply voltage	90 V to 110 V	103 V to 132 V	198 V to 242 V	207 V to 250 V

Power consumption: 27 VA max. (R6144), 26 VA max. (R6142)

External dimensions: Approx. 240 (W) $\times$ 88 (H) $\times$ 350 (D) mm

Mass: Approx. 4 kg

Accessories

Item	Model	Product code	Quantity
Power cable	A01402		1
100/120 V fuse	EAWK 0.315A		2
220/240 V fuse	EAWK 0.16A		2

Accessories (Sold separately)

Item	Model	Note
Connection cable	MI-49	2-wire cable with a banana-alligator clip (105 cm)
Connection cable	A01023	4-wire cable with a banana-alligator clip (100, 150 or 250 cm length must be specified)
Panel mount set	A02017	
Rack mount set	A02621-J	JIS standard
Rack mount set	A02621	EIA standard
Carrying case	TR16204A	